

Manufacturer

REC
Yingli

Module Class

Module Type	REC250PE	YL255C - 30b Panda Series
Solar Cell	Poly	Mono
Wafer Supplier	REC	Internal

Electrical Characteristics

Power Range (W)	250	255
Module Efficiency	15.1%	15.6%
Power Tolerance (+/-W)	-0/+5W	-0/+5W
Temp Coefficient of P _{MPP} (%/°C)	-0.40%	-0.42%
NOCT (°C)	45.7	46.0
Max System Voltage (V)	1000	1000
Reverse Current Rating (A)	25	20

Mechanical Ratings

Dimensions	1665 x 991 x 38mm	1650 x 990 x 40 (mm)
Junction Box	IP67	IP65
Weight (kg)	18	19.1
Max Wind Pressure (Pa)	2400	2400
Max Snow Load (Pa)	5400	5400

Warranty

Product Warranty (Years)	10	10
Performance Warranty (Years)	25	25
Performance Guarantee	Linear	Stepped: 10-ysrs 92.0% and 25-ysrs 82.0%
Warranted Power End of Year 1	97%	98.0%

Performance

Reduction of Efficiency At 200W/m ²	1.2%	3.5%
Antireflection Coating	Yes	No
Salt Spray Certification (Level 1-6)	6	NA : Standard not specified
Ammonia Certification	Yes	NA : Standard not specified
Estimated Yield Advantage	reference as REC	-2.6%

REC Advantages


* PTC was developed in California to better reflect module performance at higher temperatures. The PTC is calculated at expected operating temperature at 1000W/m², AM1.5. This index is influenced by NOCT & temperature co-efficient

The specification data used in this comparison has been sourced from the manufacturer and was current at the date of the revision. Efficiency curves under different irradiance levels have been imported from PVsyst v5.55.

Although REC ASA believes that the comparison is based upon reasonable assumptions, it can give no assurance that the actual results will be as set out in this comparison. REC ASA is making no representation or warranty, expressed or implied, as to the accuracy, reliability or completeness of this comparison. No part of this comparison shall form the basis of or be relied upon in connection with any contract or commitment.

This comparison may not be used or relied upon by any other party, or for any other purpose, and may not be distributed, reproduced, disseminated or quoted without the written consent of REC.

Warranted Power Conditions



Efficiency Under Different Irradiances

