


SUNTECH 175 WATT STP175S-24/Ac

High Efficiency, High Quality PV Module

Suntech's STPAc is designed and built to deliver highest efficiency and reliable power for on-grid residential and commercial systems worldwide. Relying on Suntech's well-known stringent manufacturing standards and latest PV technology, the module provides the highest possible energy output per Watt with total module efficiency of 14.1%. Superior conversion rate and exceptional low-light performance enable it to deal with the most challenging conditions of military, utility, residential and commercial installations. The module is the perfect choice for those who demand outstanding performance and exceptional uniform appearance.

FEATURES AND BENEFITS

- » High efficiency
- » Nominal 24 V DC for standard output
- » Outstanding low-light performance
- » High transparent low-iron, tempered glass
- » Unique techniques give the panel following features: esthetic appearance, with stands high wind-pressure and snow load, and easy installation
- » Unique technology ensure that problems of water freezing and warping do not occur
- » Design to meet unique demand of customer
- » 25 year module output warranty




ELECTRICAL CHARACTERISTICS

Model	STP175S-24/Ac	STP170S-24/Ac
Open-circuit voltage (Voc)	44.7V	44.4V
Optimum operating voltage (Vmp)	35.8V	35.6V
Short-circuit current (Isc)	5.23A	5.15A
Optimum operating current (Imp)	4.9A	4.8A
Maximum power at STC (Pmax)	175Wp	170Wp
Operating temperature	-40 to +85	-40 to +85
Maximum system voltage	1000V DC	1000V DC

STC: Irradiance 1000W/m² Module temperature 25 AM=1.5

Module Diagram



SPECIFICATIONS

Cell	Monocrystalline silicon solar cells
No. of cells and connections	72(6x12)
Dimension of module	1580mm×808mm×35mm
Weight	15.5kg

TEMPERATURE COEFFICIENTS


NOCT	48°C±2°C
Short-circuit current temperature coefficient	0.017 %/K
Peak power temperature coefficient	-0.34 %/K
Power tolerance	-0.48 %/K

NOCT: Nominal Operating Cell Temperature (data refer to STP165S)

OUTPUT

Cable	LAPP(4.0mm ²)
Asymmetrical Lengths	1200mm(-) and 800mm(+)
Connection	MC Plug Type IV

Normalized Isc, Voc, Pmax VS. Module Temperature Characteristics



Characteristics Module IV Graph 175W

