



WATER



TROJAN[®]

MARINE/RV

- Pro anglers and boaters trust Trojan Marine/RV™ to start their engines and power their gear in the toughest of conditions; you can too!
- Trojan Marine/RV™ products are designed to deliver maximum durability, reliability and performance for more hours of fun on the water.
- Trojan Marine/RV™ products are backed by outstanding technical support. Call 800-423-6569 or 562-946-8381 or visit www.trojanbattery.com.
- Trojan offers a full line of starting, dual purpose and deep cycle batteries, including maintenance free, non-spillable AGM products. All are available through Trojan's worldwide Master Distributor Network and select outdoor retailers.

Including

MINN KOTA

Marine Batteries by Trojan™



MORE POWER. LONGER LIFE.

BCI Group Size	Type	Voltage	Capacity ^A (Minutes)		Cranking Performance		5 Hr. ^D Rate (AH)	20 Hr. ^E Rate (AH)	Dimensions ^F inches (mm)			Weight lbs (kg)
			@25 Amps	@75 Amps	CCA ^B @0°F	CA ^C @32°F			L	W	H	
TROJAN MARINE/RV DEEP CYCLE												
GC2	T-105	6	447	115	-	-	185	225	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	62 (28)
GC2	T-125	6	488	132	-	-	195	240	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	66 (30)
GC2H	T-145	6	530	145	-	-	215	260	10 3/8 (264)	7 1/8 (181)	11 5/8 (295)	72 (33)
N/A	J305H	6	745	195	-	-	285	335	11 5/8 (295)	7 (178)	14 3/8 (365)	97 (44)
N/A	L16H	6	885	225	-	-	345	420	11 5/8 (295)	7 (178)	16 3/4 (424)	121 (55)
24	SCS150	12	150	36	530	650	80	100	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	50 (23)
27	SCS200	12	200	52	620	760	95	115	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	60 (27)
30H	SCS225	12	225	57	665	820	105	130	13 15/16 (355)	6 3/4 (171)	9 7/8 (251)	66 (30)
N/A	J185H	12	415	110	-	-	180	215	15 (381)	7 (178)	14 5/8 (371)	122 (55)
TROJAN MARINE/RV STARTING												
24	24SM-650	12	85	-	520	635	-	-	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	38 (17)
24	24SM-850	12	125	-	700	860	-	-	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	43 (20)
24	24SM-1000	12	165	-	825	1025	-	-	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	49 (22)
27	27SM-1100	12	205	-	860	1050	-	-	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	55 (25)
TROJAN MARINE/RV MAINTENANCE FREE STARTING												
24	24SM-850MF	12	125	-	700	860	-	-	10 3/16 (258)	6 1/2 (165)	9 7/16 (239)	43 (20)
24	24SM-1000MF	12	165	-	825	1025	-	-	10 3/16 (258)	6 1/2 (165)	9 7/16 (239)	49 (22)
TROJAN MARINE/RV DUAL PURPOSE												
24	24TMS	12	125	34	470	575	62	72	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	41 (19)
24	24TM	12	135	34	550	675	66	85	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	44 (20)
27	27TMS	12	145	39	550	675	73	85	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	48 (22)
27	27TM	12	160	38	630	770	79	105	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	50 (23)
TROJAN MARINE/RV AGM DUAL PURPOSE												
24	24-AGM	12	130	-	440	620	61	80	10 13/16 (259)	6 5/8 (168)	8 7/8 (226)	52 (24)
27	27-AGM	12	175	-	560	780	76	100	12 (305)	6 5/8 (168)	9 3/16 (233)	66 (30)
31	31-AGM	12	190	-	720	950	83	110	13 1/16 (208)	6 7/8 (174)	8 11/16 (221)	71 (32)
4D	4D-AGM	12	325	-	1110	1420	131	165	20 7/8 (530)	8 1/4 (209)	9 3/8 (237)	115 (52)
8D	8D-AGM	12	460	-	1450	1850	179	230	20 1/2 (521)	10 9/16 (269)	8 7/8 (226)	155 (70)
GC2	6V-AGM	6	385	-	1100	1400	154	200	10 1/4 (260)	7 1/16 (179)	10 5/8 (270)	65 (29)
MINN KOTA BY TROJAN DEEP CYCLE - 12 VOLT												
24	MK24DC	12	140	36	440	540	70	85	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	47 (21)
27	MK27DC	12	175	45	530	650	85	105	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	55 (25)
30H	MK31DC	12	190	50	575	710	100	120	13 15/16 (355)	6 3/4 (171)	9 7/8 (251)	66 (30)
MINN KOTA BY TROJAN DUAL PURPOSE STARTING/DEEP CYCLE - 12 VOLT												
24	MK24DP	12	125	34	470	575	62	72	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	41 (19)
27	MK27DP	12	145	39	550	675	73	85	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	48 (22)
MINN KOTA BY TROJAN STARTING - 12 VOLT												
24	MK550ST	12	65	-	420	515	-	-	11 1/4 (286)	6 3/4 (171)	9 3/4 (248)	36 (16)

- A. Reserve Capacity or Capacity - The number of minutes a battery can be discharged at 25 or 75 amps at 27°C (80°F) and maintain a voltage above 1.75 v/cell.
- B. C.C.A. (Cold Cranking Amps) - The discharge load in amperes which a new, fully charged battery can maintained for 30 seconds at -18° C (0°F) at a voltage above 1.2 v/cell.
- C. C.A. (Cranking Amps) - The discharge load in amperes which a new, fully charged battery can maintained for 30 seconds at 0°C (32°F) at a voltage above 1.2 v/cell. This is sometimes referred to as marine cranking amps @ 0°C (32°F) or M.C.A. @ 0°C (32°)
- D. 5 hour rate is based on IEC (International Electrotechnical Commission) temperature standard of 30°C (86°F).
- E. 20 hour rate is a BCI sanctioned rating expressing ampere hours required to achieve an end voltage of 1.75 v/cell at 27°C (80°F) and represents the battery's maximum capacity.
- F. All dimensions taken from bottom of battery to top of terminal. Heights may vary according to type of terminals specified.

Terminal Configurations



1- "L" Terminal (LT)



2-Automotive Post (AP)



6 - Low Profile Terminal (LPT)



7- AP and Stud Terminal (DT)



8- Dual Wingnut Terminal (DWNT)



9- Marine Dual Terminal (APW)



10-Stud Terminal



11- Universal Terminal (UT)



12- Wingnut Terminal (WNT)



For a Master Distributor near you, call 800-423-6569 or 562-946-8381
or visit www.trojanbattery.com.
Clean energy for life™