

# ST2752UX-AU

## Liquid Cooling Energy Storage System



### LOW COSTS

- Highly integrated ESS for easy transportation and O&M
- All pre-assembled, no battery module handling on site
- 8 hour installation to commission, drop on a pad and make electrical connections



### SAFE AND RELIABLE

- Integrated DC/DC converters actively limit fault current
- DC electric circuit safety management includes fast breaking and anti-arc protection
- Multi level battery protection layers formed by discreet standalone systems offer impeccable safety



### EFFICIENT AND FLEXIBLE

- Intelligent liquid cooling ensures higher efficiency and longer battery cycle life
- Modular design supports parallel connection and easy system expansion
- IP54 outdoor cabinet and optional C5 anti-corrosion



### SMART AND ROBUST

- Fast state monitoring and faults record enables pre-alarm and faults location
- Integrated battery performance monitoring and logging



Type designation	ST2752UX-AU
<b>Battery Data</b>	
Cell type	LFP
Battery capacity (BOL)	2752 kWh
System output voltage range	1036.8 ~ 1401.6 V
<b>General Data</b>	
Dimensions of battery unit (W * H * D)	9340*2600*1730mm
Weight of battery unit	26,400kg
Degree of protection	IP54
Operating temperature range	-30 to 50 °C (> 45 °C derating)
Relative humidity	0 ~ 95 % (non-condensing)
Max. working altitude	3000 m
Cooling concept of battery chamber	Liquid cooling
Fire safety standard / Optional	Fused sprinkler heads, NFPA 69 explosion prevention and ventilation IDLH gases
Communication interfaces	RS485, Ethernet
Communication protocols	Modbus RTU, Modbus TCP
Compliance	CE, IEC 62477-1, IEC 61000-6-2, IEC61000-6-4, IEC62619
<b>2 HOURS APPLICATION-ST2752UX*4-4980UD-MV</b>	
BOL kWh (DC)	11,008 kWh
ST2752UX Quantity	4
PCS Model	SC4980UD-MV
<b>4 HOURS APPLICATION-ST2752UX*8-4980UD-MV</b>	
BOL kWh (DC)	22,016 kWh
ST2752UX Quantity	8
PCS Model	SC4980UD-MV
<b>Grid Connection Data</b>	
Max.THD of current	< 3 % (at nominal power)
DC component	< 0.5 % (at nominal power)
Power factor	> 0.99 (at nominal power)
Adjustable power factor	1.0 leading ~ 1.0 lagging
Nominal grid frequency	50 / 60 Hz
Grid frequency range	45 ~ 55 Hz / 55 ~ 65 Hz
<b>Transformer</b>	
Transformer rated power	5,000 kVA
LV / MV voltage	0.55 kV / 11 ~ 35 kV (Dy11y11)
Transformer cooling type	ONAN (Oil Natural Air Natural)
Oil type	Mineral oil (PCB free) or degradable oil on request

