

• YOUR  
• SMART  
• ENERGY



# SMILE5

RESIDENTIAL SERIES

## POWER

5 kW Inverter

## CAPACITY

10.1 / 13.3 kWh

Battery Modular

Expandable to 80 kWh



5kW Single Phase Hybrid Inverter

Fast Response

UPS Ability

24/7 Monitoring

VPP Ready



# SMILE5



Model		SMILE5	
<b>System Specification</b>			
Rated Output Power	5000 W		
Rated Output Apparent Power	5000 VA		
Capacity Range	10.1 ~ 60.6 kWh(96% DoD)	13.3 ~ 80 kWh(100% DoD)	
Usable Capacity Range	9.7 ~ 58.1 kWh	13.3 ~ 80 kWh	
Battery Chemistry	LFP (LiFePO4)		
IP Protection	IP65		
Warranty	10 Year Product Battery Warranty		

<b>Inverter Technical Specification</b>			
Model	SMILE5-INV	Rated Output Apparent Power (Backup Port)	5000 VA
Coupling	Hybrid	Rated Output Current (Backup Port)	21.7 A
Max. PV Input Power	7500 W	Max. AC Output Current (Backup Port)	21.7 A
Max. PV Input Current	15 A / 15 A	Rated Frequency	50 / 60 Hz
Max. PV Input Voltage	550 V	Max Inverter Efficiency	96.50%
Start-up input voltage	90 V	Backup	UPS
Rated PV Input Voltage	360 V	Communication	Ethernet / WIFI
MPPT Number/Max. Input Strings Number Per MPPT	2/1	Humidity	0 ~ 90% (No Condensing)
MPPT Voltage Range	70 ~ 540 V	Dimension (W x D x H)	610 x 210 x 627 mm
Max. PV Short-circuit Current	18 A / 18 A	Weight	27.7 kg
Max. Charging/Discharging Current	100 A	Operating temperature	-25 ~ 60 °C
Max. Charging/Discharging Power	5000 W	Overvoltage Category	DC II AC III
Rated Voltage	230 V	Active-islanding Method	Frequency shift
Max. AC input Power (Grid Port)	7500 W	Country of Manufacture	CHINA
Rated Output Current (Grid Port)	21.7 A	Safety	IEC 62109
Max. AC Output Current (Grid Port)	21.7 A	EMC	EN 61000-6-1 / EN 61000-6-3
Rated Output Apparent Power (Grid Port)	5000 VA	Grid Regulation	AS4777.2.2020

<b>Battery Technical Specification</b>		
Module Model	SMILE-BAT-10.1P	SMILE-BAT-13.3P
Module Capacity	10.1 kWh	13.3 kWh
Module Nominal Voltage	48 V	48 V
Operating Temperature Range	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*
Max. Modules in Parallel	6	6**
Max. Charging / Discharging Current	100 A	100 A
Cycle Life	8000***	8000***

\* Max. charge/discharge current derating will occur related to temperature and SOC.  
 \*\* ≥2 needs to install expansion pack  
 \*\*\* Under specific test conditions



#### Alpha ESS Co., Ltd.

+86 513 8060 6891  
 info@alpha-ess.com  
 www.alphaess.com  
 Jiuhua Road 888, Nantong  
 High-Tech Industrial  
 Development Zone, Nantong,  
 Jiangsu Province, China

#### Alpha ESS Suzhou Co., Ltd.

+86 512 6828 7609  
 info@alpha-ess.com  
 www.alphaess.com  
 Building 10-A, Canal Town Industrial  
 Park, 99 Taihu E Rd, Wuzhong District,  
 Suzhou, Jiangsu Province, China

#### Alpha ESS Europe GmbH

+49 610 3459 1601  
 europe@alpha-ess.de  
 www.alphaess.de  
 Paul-Ehrlich-Straße 1a,  
 Langen, Hessen D-63225  
 Germany

#### Alpha ESS Australia Pty. Ltd.

+61 02 9000 7676  
 Australia@alpha-ess.com  
 www.alphaess.com  
 8/15-21 Gibbes Street, Chatswood,  
 NSW 2067 Australia

#### Alpha ESS Italy S.r.l.

+39 339 462 4288  
 info@alpha-ess.it  
 www.alphaess.com  
 Via Don Minzoni, 17,  
 Calenzano Firenze 50041 Italy

#### Alpha ESS UK Ltd.

+44 145 354 5222  
 info@alpha-ess.com  
 Drake house, Long  
 street, Dursley, g11  
 4hh UK

#### Alpha ESS International Pte. Ltd.

+65 6513 1125 / +65 6513 1126  
 Singapore@alpha-ess.com  
 2 Corporation Road #01-06A  
 Corporation Place 618494  
 Singapore

#### Alpha ESS USA, Inc.

+1 408 368 7828  
 usa@alpha-ess.com  
 Unit 5 2180 S Ivanhoe  
 St, Denver, CO 80222  
 USA

#### Alpha ESS Korea Co., Ltd.

info@alpha-ess.com  
 2F, 19-4, Nohyeong 11-gil,  
 Jeju-si, Jeju-do, Republic of  
 Korea